Estesa

Protech Line

Estesa expanded metal mesh is available in **customised formats**. With its **52,8% frontal opening**, it is one of the most open meshes and has excellent transparency and a **striking effect** in **façade** cladding applications. Bespoke formats can be requested to optimise **cladding projects**. Scroll down the page to rotate a 3D model in various positions and see some of the projects where Estesa mesh type has been used.

Product data:
R 270 x 100 (100) - 30 x t
Final thickness: 49.00 mm
Open Area: 52.80 %
Open Area MAX: 83 %

Materiale	Nome	mm	Peso kg/m2	Sheet On demand
Carbon steel	R 270 x 100 (100) - 30 x 1,5	1.5	7.5	✔
Carbon steel	R 270 x 100 (100) - 30 x 2	2.0	10.0	✔
Sendzimir carbon steel	R 270 x 100 (100) - 30 x 1,5	1.5	7.5	✔
Sendzimir carbon steel	R 270 x 100 (100) - 30 x 2	2.0	10.0	✔
Aluminium	R 270 x 100 (100) - 30 x 1,5	1.5	2.5	✔
Aluminium	R 270 x 100 (100) - 30 x 2	2.0	3.4	✔
Aluminium	R 270 x 100 (100) - 30 x 3	3.0	5.0	✔

Riferimenti

Nome	=	Geom DL x DCn (DCr) - av x sp
Geom	=	**E**sagonale, **R**omboidale, **Q**uadra, **T**onda, **S**pianata
DL	=	Diagonale Lunga
DCn	=	Diagonale Corta nominale (riferimento interno)
DCr	=	Diagonale Corta reale
av	=	Avanzamento
sp	=	Spessore
spFin	=	Spessore finale
v/p %	=	% vuoto su pieno
Larg - DL	=	Larghezza in direzione DL
Lung - DC	=	Lunghezza in direzione DC (direzione di stiratura)

Dimensioni

Bobine - Fogli - Rotoli



Dimensione maglia



Facciata a vista